

BLENDER SPECIFICATION SHEET



Double Mix Gas Blender

The mixed gas double blender can be used for systems that dispense more than one type of beer requiring separate blends of CO₂ and N₂.

Size: 9.5" wide (including mounting flanges x 10" high x 4.5" deep

Hook-Up: Two inlet lines and two outlet lines.

Fittings: Panel comes with standard 1/4" female NPT fittings. Hose barbs can be 1/4", 5/16", and 3/8" size.

Accuracy and Flow Range: Maintains accuracy of +/- 2% of full scale or better within the flow range of .4 to 40 liters per minute (.85 to 85 cubic feet per hour).

Standard Flow: Up to 30 kegs/hr. dispensed.

High Flow Blender: Up to 60 kegs/hr. dispensed. Used for systems requiring two blends of CO₂ and N₂ that operate with higher than usual gas flow.

Inlet Pressures: 55-150 psi, however, panel can be set to match any conditions. Blender tuned at inlet pressure of existing system. Standard 55 and 70 psi.

Outlet Pressures: Adjustable outlet pressures of 0-60 psi. The maximum outlet pressure will always be 10 psi lower than the lowest inlet pressure. The panel can also be ordered with outlet pressure set to custom ranges.



1993-7 Moreland Pkwy ♦ Annapolis, MD 21401

Tel: (410) 268-0714 ♦ Fax: (410) 268-8300

800-925-3818