

## BLENDER SPECIFICATION SHEET



**Single Mix Gas Blender:** dispenses one style of beer, the single blend blender blends CO<sub>2</sub> and N<sub>2</sub> to your specifications.

**Size:** 9.5" wide (including mounting flanges x 10" high x 4.5" deep

**Hook-Up:** Two inlet lines and one outlet line.

**Fittings:** Panel comes with standard 1/4" female NPT fittings. Hose barbs can be 1/4", 5/16", and 3/8" size.

**Accuracy and Flow Range:** Maintains accuracy of +/- 2% of full scale or better within the flow range of .4 to 40 liters per minute (.85 to 85 cubic feet per hour).

**Standard Flow:** Up to 15 kegs/hr. dispensed.

**High Flow Blender:** Up to 30 kegs/hr. dispensed. Used for systems requiring only one blend of CO<sub>2</sub> and N<sub>2</sub> that operate with higher than usual gas flow.

**Inlet Pressures:** 55-150 psi, however, panel can be set to match any conditions. Blender tuned at inlet pressure of existing system. Standard 55 and 70 psi.

**Outlet Pressures:** Adjustable outlet pressures of 0-60 psi. The maximum outlet pressure will always be 10 psi lower than the lowest inlet pressure. The panel can also be ordered with outlet pressure set to custom ranges.

