



AC Beverage (800)925-3818 The Single Source for Quality Draught Equipment, Superior System Installation and Exceptional Draft Services.



Trumix® Single 60/40 Gas Blending Panel

The Trumix® Gas Blending Panel is a small wall-mounted unit that tucks neatly and safely out of the way. It is easy to install and is extremely dependable. The Trumix® requires no electricity, on-going maintenance or adjustment. It can be used with all sources of clean nitrogen and CO2 including high pressure cylinders, and bulk tanks.

Features:

- Standard Flow: Up to 30 kegs/hr. (15 kegs/hr. per blend) dispensed.
- On-site accurate gas blending.
- More cost-effective than pre-mixed cylinders.

Pressures:

Inlet Pressures: 55-150 psi, however, panel can be set to match any conditions. Blender tuned at inlet pressure of existing system. Standard 55 and 70 psi.

Outlet Pressures: Adjustable outlet pressures of 0-60 psi. The maximum outlet pressure will always be 10 psi lower than the lowest inlet pressure.

Specifications:

Type	Single Gas Blending Panel
Lager Blend	60% CO2 & 40% Nitrogen
Dimensions	11" W x 15" H x 6" D
Standard Gas Flow	Up to 30 kegs/hr. (15 kegs/hr. per blend) dispensed
Outlet Pressure	Adjustable
Installation	Wall Mount

